

HUMBUCKER PICKUP

SH-4

- Active, noise-free design
- Combination of magnetic pickup and microphone, which records the body resonance
- Separate volume control for magnetic and microphone pickup
- Power supply via 2 × CR2032 batteries
- Battery life max. 160 h
- 70 cm cable with 1/4" coupling
- Dimensions :107 × 34.5 × 19.5 mm
- Balanced tone
- High sensitivity
- Incl. reusable adhesive



RackTuner

RACKTUNER

Pitchmaster

SPECIFICATIONS:

Inputs: Two on Front Panel, One on Back Panel

Outputs: One on Back Panel

Front Panel Tuning Range: +/-50 Cents

Calibration Range: 436hz - 445hz

Mute Switches: Manual Switch on Front Panel, Optional

Footswitch Jack on front panel (Momentary footswitch)

Other Switches: Precision Mode, Note Selector

Size: 482mm x 105mm x 44mm

Weight: 2 kg

Input Impedance: $\geq 1.5M \Omega$

Output Impedance: $\leq 1K \Omega$

Power Consumption: $\leq 1W$



Acoustic Preamp with Looper

- Acoustic Preamp with Looper
- With reverb and chorus and Compact phrase looper
- Separate controls for reverb and chorus and Compact phrase looper
- Volume, Bass, Treble, Gain, Shape, Phase controls
- Recording time up to 10 minutes
- Unlimited overdubbing
- Ground / lift
- Status LEDs
- Instrument input and Line input
- Outputs: jack / headphone / balanced DI XLR
- Operation with 9 V power supply
- Power consumption: 190 mA
- Dimensions: 128 x 93 x 58 mm
- Weight: 465 g



Storm Bomb 100

Ultra-compact Power Amp pedal for electric guitar and bass
Suitable for direct input from preamps, pedals or effects units

- Master volume control
- Mono- / stereo inputs (2 × 1/4" jack)
- Line stereo input (3.5 mm jack)
- Stereo speaker outputs (2 × 1/4" jack)
- Headphones output (3.5 mm jack)
- Mute switch with LED
- Mains adapter included
- Output power: 2 × 50 W @ 4 Ω
- Impedance suitable for speaker boxes with 4 – 16 Ω
- Power supply external mains adapter (24 V / 5.0 A, centre positive) supplied
- Dimensions: 74 × 59 × 124 mm
- Weight: 330 g

